

Transfer-press PT-17 Swing S

Product Information

PT-17 Swing S is a transfer press which opens automatically after the pressing operation through an electromagnetic function. The heating plate swings independently to the side.

PT-17 Swing S has a microprocessor with a digital display for accurate presetting of the press time and temperature. A pre- and after-press-time is programmable.

PT-17 Swing S, the standard model has a plate in the dimension of 38×45 cm. Standard equipment is supplied with a solid base table. The following alternative items are available:

Heating plate: 40×50 cm, 28×38 cm, 20×20 cm Basis plate: 40×50 cm, 28×38 cm, 20×20 cm, 12×12 cm, 10×45 cm (sleeve plate),

20 x 43 x 38 cm (umbrella plate).

PT-17 Swing S can ideally be used for the serial transfer of transfers on T-shirts, sportswear, umbrellas and bags. The fitting of alternative heating and base plates can be performed quickly and is very user-friendly.

PT-17 Swing S bears the CE Marking in accordance with the EC conformity declaration according to EC directives for machines 2006/46EC.

The heating press is supplied with a detailed instruction manual with information of the equipment technology, safety precautions, start-up procedure, programming of the electronic system and maintenance.



Technical Data

Dimension of the table 40 x 50 cm

Dimension of the device 184 x 86 x 94 cm

Weight (incl. packaging) 95 kg

Power/Performance 10,5 A / 230 V

Temperature 220 °C (max.)

Precision of temperature $+/-1~^{\circ}\mathrm{C}$

Heating Power 2,4 kW

Preheating time 12 min. for 180 °C

Time setting 59 sec. – 9 min. (max.)

Pressing power 1.050 kp (max.)

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

Internet:

53424 Remagen - GERMANY

Phone: +49 (0) 2642 - 9836 0 Fax: +49 (0) 2642 - 9836 37 E-Mail: info@poli-tape.de

www.poli-tape.de

30/01/2012

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.