

Product Information

Self adhesive PVC film with a reflection free, matt surface. The modified medium tack acrylic adhesive can be peeled off without any residues, even after a long application time.

POLI-Mask 2605 can be cut on all CAD/CAM plotters. For transferring the stencil we recommend PT 190 as an Application Tape.

Universally used for all sandblast applications including stone, marble, glass or plastics. The product performs with a high rebound elasticity which shows excellent contour sharpness.

During application the following conditions are taken into consideration:

Injector-technology

Range of pressure: 2-8 bar

Granulation: 150-250 μ

Pressure beam-technology

Range of pressure: 0,5-3,0 bar

Granulation: 150-250 μ

Only mineral abrasives such as dross, quartz sand, korund or glass-pearls should be used. Abrasives like steel shot or gift shot are not suitable.

Technical Data

Carrier:	PVC film, blue, matt	
Adhesive:	Acrylic	
Liner:	Silicone paper (120g/m ²)	
Adhesion [N/cm]:	1,60	+/- 10 %
Thickness [mm]:	0,35	+/- 5 %

Standard Dimensions

1.220 mm x 20 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.