

Product Information

Self adhesive stencil tape on the basis of a dimensionally stable polypropylene film with outstanding solvent resistance.

Suitable for lettering and spray mask applications on all varnished, glass, plastic and metal surfaces. POLI-MASK 288 can be used on flexible materials like PVC awnings and banner material as well.

Especially to be emphasised are the following properties:

- The detachable adhesive has an excellent durability on solvent contained screen-printing and awning materials. Can be easily removed without any residues.
- The polypropylene film possesses an optimal flat surface. Even if there is any solvent influence, no surface changes like creases or blistering is guaranteed.
- Outstanding sharp outline edges, therefore colour undermining on the outline edges are completely excluded.
- Can be used on freshly varnished surfaces without leaving any residues. Ideal for multi-colour lettering.
- The stencil tape can be cut with neat, sharp and accurate outlines, it is easy to weed and it can be easily transmitted without any problems.

Technical Data

Carrier:	Polypropylene film, blue, translucent	
Adhesive:	Acrylic	
Liner:	Silicone paper, white (140g/m ²)	
Adhesion [N/cm]:	1,70	+/- 10 %
Thickness [mm]:	0,10	+/- 5 %

Standard Dimensions

1.220 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0
Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.