

## Product Information

Transparent Application Tape made of an embossed cast Polypropylene film. PT 95 can be torn by hand in both directions. The product offers dimensional stability and excellent lay-flat properties.

Due to the medium tack acrylic adhesive, computer cut letters, images and logos, made of cast or calendered CAD/CAM plotter films can easily be transferred.

Especially to be emphasised are the following properties:

- The excellent lay-flat property guarantees excellent lamination without wrinkles, even on large motifs.
- To guarantee an easy processing, the film can be torn by hand in both directions.
- Easy unwinding of the film with low static charge.
- The acrylic adhesive is specially developed and has a constant high adhesive strength level. It can be removed without residues, even after a long period of application.
- Suitable for dry and wet applications.

## Technical Data

<b>Carrier:</b>	Polypropylene film, pyramid surface	
<b>Adhesive:</b>	Acrylic, modified	
<b>Adhesion [N/cm]:</b>	1,70	+/- 10 %
<b>Thickness [mm]:</b>	0,14	+/- 5 %

## Standard Dimensions

1.220 mm x 100 m

1.000 mm x 100 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

### POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17  
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0  
Fax: +49 (0) 2642 – 9836 37

E-Mail: [info@poli-tape.de](mailto:info@poli-tape.de)  
Internet: [www.poli-tape.de](http://www.poli-tape.de)

12/08/2016

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.