

Product Information

Application Tape based on a special impregnated paper coated with a natural rubber (Low Tack).

Suitable for application of large self adhesive lettering, logos, stickers and silk-screen prints, if easy removal is required.

Especially to be emphasised are the following properties:

- The natural rubber ensures a constant adhesion within a small tolerance.
- The Ageing- and UV-stabilised natural rubber can be removed without residues even after a longer period.
- The Application Tape can be rewound easy from the roll and shows excellent lay-flat properties and is dimensionally stable.

Technical Data

Carrier:	Special paper, impregnated	
Adhesive:	Natural rubber	
Adhesion [N/cm]:	1,30	+/- 10 %
Thickness [mm]:	0,10	+/- 5 %

Standard Dimensions

1.220 mm x 100 m
1.220 mm x 91,4 m
1.000 mm x 100 m
1.000 mm x 91,4 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.