

# PT 122

#### **Product Information**

Application Tape based on a special high tensile impregnated paper coated with a natural rubber (Medium Tack). The tape is suitable for transferring lettering and symbols cut from all qualities of self adhesive vinyls.

Especially to be emphasised are the following properties:

- · Ageing- and UV-stabilised natural rubber.
- The Application Tape is easy to unroll and position and will not stretch or curl.
- · Constant adhesion within a small tolerance.
- · Suitable for wet application.

#### **Technical Data**

Carrier: Special paper, impregnated

Adhesive: Natural rubber

Adhesion [N/cm]: 2,10 +/- 10 %

Thickness [mm]: 0,10 +/- 5%

### Standard Dimensions

1.220 mm x 100 m

1.220 mm x 91,4 m

1.000 mm x 100 m

1.000 mm x 91,4 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

### POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

53424 Remagen - GERMANY

Phone: +49 (0) 2642 - 9836 0 Fax: +49 (0) 2642 - 9836 37 E-Mail: info@poli-tape.de Internet: www.poli-tape.de 28/07/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.