

## Product Information

POLI-TACK 810 is a thin and flexible, horizontal and vertical tear resistant, aluminized polyester film with an acrylic adhesive.

POLI-TACK 810 is preferentially used for protection of screen print frames, isolation and decorative applications.

Especially to be emphasised are the following properties:

- Good resistance against ageing and chemicals.
- Excellent isolation against the impact of humidity and temperature.

## Technical Data

<b>Carrier:</b>	PET-film, silver metallized	
<b>Adhesive:</b>	Acrylic	
<b>Adhesion [N/cm]:</b>	3,20	+/- 10 %
<b>Thickness [mm]:</b>	0,06	+/- 5 %
<b>Temperature resistance [°C]:</b>	-40 / +120	

## Standard Dimensions

1.000 mm x 66 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.