

## Product Information

Transparent Application Tape with a silicone paper-liner, based on a polypropylene film embossed on one side that is dimensionally stable, easy to unroll, position and will not stretch or curl.

Suitable for transferring self adhesive signs, logos and lettering produced from cast or calendered CAD/CAM plotter films with matt or brilliant surface.

Especially to be emphasised are the following properties:

- Excellent positioning due to the integrated square print on the PP film. Furthermore, the imprint serves as an optimal cutting assistant to enable accurate work.
- As the tape does not curl, wrinkling is avoided during lamination of large lettering. The film adjusts perfectly to the surface.
- The plasticiser resistant adhesive guarantees a strong initial tack to all types of vinyl films. The Application Tape is easily removed without leaving any residue, even after being left for a period of time.
- Suitable for wet application.
- The film can be torn transversally, which facilitates handling.
- The embossed surface allows the film to be easily unrolled without accumulation of static electricity.
- Silicone paper enables the applicator to store plotter films easily, before they are applied.

## Technical Data

<b>Carrier:</b>	Polypropylene film, Orange peel surface (grey square print)
<b>Liner:</b>	Silicone paper (90g/m <sup>2</sup> ),
<b>Adhesive:</b>	Acrylic
<b>Adhesion [N/cm]:</b>	1,1            +/- 20 % (Finat FTM1 after 20 min on steel)
<b>Thickness [mm]:</b>	0,11            +/- 10 %

## Standard Dimensions

1.200 mm x 50 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

### POLI-TAPE Klebfolien GmbH

Zeppelinstraße 17  
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0  
Fax: +49 (0) 2642 – 9836 37

E-Mail: [info@poli-tape.de](mailto:info@poli-tape.de)  
Internet: [www.poli-tape.de](http://www.poli-tape.de)

10/02/2020

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.