



ULTIMATE PRINT TRANSPARENT SOFT 4034 MATT

Product Information

Heat-sealable, printable Polyurethane-film (transparent) suitable for white textiles.

ULTIMATE PRINT TRANSPARENT SOFT 4034 MATT is a two-layer transfer film being coated with a hotmelt on the non-covered printable side. The upper side of the film after the application process is based on a transparent, UV-resistant polyurethane.

ULTIMATE PRINT TRANSPARENT SOFT 4034 MATT is compatible with all current printers using ECO-solvent and solvent. The PET liner allows even filigree motifs to cut by all current CAD/CAM plotters after printing. After weeding the heat transfer is done with the original carrier.

A matt PET-film on top of the image during the thermal transfer gives a brilliant semi-matt finish. After heat-transfer we recommend removing the PET-liner after a short period of cooling down to room temperature.

The transfer film is used for motifs and logos on sport, leisure and work wear.

The raw materials are ecologically inert, do not contain PVC, plasticizers or heavy metals (in accordance with OEKO-TEX STANDARD 100 Class I).

We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.

Standard Dimensions

500 mm x 10 m
500 mm x 25 m
750 mm x 25 m*
1.000 mm x 25 m*
1.524 mm x 25 m*

*Non-standard dimension. Extended delivery times may occur.

Technical Data

Transfer Film:	Polyurethane, cast
Adhesive:	Polyurethane-hotmelt
Thickness [mm]:	0,05 +/- 10 %
Liner:	PET-film, non adhesive

Transfer Conditions

Temperature:	160 °C
Pressure:	2,5 - 3,0 bar [medium pressure]
Time:	15 sec.

Wash Resistance / Printing

Wash resistance:	40 °C Only colour or mild detergent. Wash textiles inside out. Tumble dryable.
Printing:	On reverse, mirror-inverted.

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH
Zeppelinstraße 17
53424 Remagen – GERMANY

Phone: +49 2642 – 98 36 0
Fax: +49 2642 – 98 36 37

E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.